

Product information

78 03 125

Electronic Super Knips®

DIN ISO 9654




- Cutting edge hardness approx. 54 HRC •
- INOX tool steel
- Precision pliers for ultra fine cutting work, e. g. in electronics and fine ٠ mechanics
- Ground, very sharp cutting edges without bevel •
- Precisely shaped tips cut wires close to a surface from Ø 0.2 mm
- Shear cut with controlled micro cutting edge misalignment for the most • precise cutting of even the thinnest of wires and for a long service life Joint with stainless steel rivet •
- Extremely smooth movement for minimum operator fatigue ٠
- With opening spring and opening limiter

General

MM 🗾

| EAN4003773035381HeadpolishedHandleswith multi-component gripsWeight56 gDimensions125 x 65 x 13 mmStandardDIN ISO 9654ReachnoRohSnoTechnical detailsCutting capacities medium hard wire (aiameter)Ø 1.0 mmCutting capacities soft wire (diameter)Ø 0.2 – 1.6 mmJaw length (B)9 mm | General | |
|--|---|----------------------------|
| HeadpolishedHandleswith multi-component gripsWeight56 gDimensions125 x 65 x 13 mmStandardDIN ISO 9654ReachnoRohSnoTechnical detailsCutting capacities medium hard wire (diameter)Ø 1.0 mmCutting capacities soft wire (diameter)Ø 0.2 – 1.6 mmJaw length (B)9 mmJaw thickness (joint) (D)7.5 mm | Article No. | 78 03 125 |
| Handleswith multi-component gripsWeight56 gDimensions125 x 65 x 13 mmStandardDIN ISO 9654ReachnoRohSnoTechnical detailsCutting capacities medium hard wire (diameter)Ø 1.0 mmCutting capacities soft wire (diameter)Ø 0.2 – 1.6 mmJaw length (B)9 mmJaw thickness (joint) (D)7.5 mm | EAN | 4003773035381 |
| Weight56 gDimensions125 x 65 x 13 mmStandardDIN ISO 9654ReachnoRohSnoTechnical detailsCutting capacities medium hard wire (diameter)Ø 1.0 mmCutting capacities soft wire (diameter)Ø 0.2 – 1.6 mmJaw length (B)9 mmJaw thickness (joint) (D)7.5 mm | Head | polished |
| Dimensions125 x 65 x 13 mmStandardDIN ISO 9654ReachnoRohSnoTechnical detailsCutting capacities medium hard wire (diameter)Ø 1.0 mmCutting capacities soft wire (diameter)Ø 0.2 – 1.6 mmJaw length (B) Jaw thickness (joint) (D)9 mm | Handles | with multi-component grips |
| StandardDIN ISO 9654ReachnoRohSnoTechnical detailsCutting capacities medium hard wire (diameter)Ø 1.0 mmCutting capacities soft wire (diameter)Ø 0.2 – 1.6 mmJaw length (B)9 mmJaw thickness (joint) (D)7.5 mm | Weight | 56 g |
| ReachnoRohSnoTechnical detailsCutting capacities medium hard wire (diameter)Ø 1.0 mmCutting capacities soft wire (diameter)Ø 0.2 – 1.6 mmJaw length (B)9 mmJaw thickness (joint) (D)7.5 mm | Dimensions | 125 x 65 x 13 mm |
| RohSnoTechnical detailsCutting capacities medium hard wire (diameter)Ø 1.0 mmCutting capacities soft wire (diameter)Ø 0.2 – 1.6 mmJaw length (B)9 mmJaw thickness (joint) (D)7.5 mm | Standard | DIN ISO 9654 |
| Technical detailsCutting capacities medium hard wire (diameter)Ø 1.0 mmCutting capacities soft wire (diameter)Ø 0.2 – 1.6 mmJaw length (B)9 mmJaw thickness (joint) (D)7.5 mm | Reach | no |
| Cutting capacities medium hard wire (diameter)Ø 1.0 mmCutting capacities soft wire (diameter)Ø 0.2 – 1.6 mmJaw length (B)9 mmJaw thickness (joint) (D)7.5 mm | RohS | no |
| (diameter)Ø 0.2 – 1.6 mmDutting capacities soft wire (diameter)Ø 0.2 – 1.6 mmJaw length (B)9 mmJaw thickness (joint) (D)7.5 mm | Technical details | |
| Jaw length (B)9 mmJaw thickness (joint) (D)7.5 mm | | Ø 1.0 mm |
| Jaw thickness (joint) (D) 7.5 mm | Cutting capacities soft wire (diameter) | Ø 0.2 – 1.6 mm |
| | Jaw length (B) | 9 mm |
| Head width (A) 13.5 mm | Jaw thickness (joint) (D) | 7.5 mm |
| | Head width (A) | 13.5 mm |



KNIPEX Quality – Made in Germany



| Classification | |
|----------------|------------|
| eCl@ss 5.1.4 | 21040302 |
| ETIM 5.0 | EC000165 |
| ETIM 6.0 | EC000165 |
| proficl@ss 6.0 | AAA949c004 |
| UNSPSC 13.1 | 27112149 |

technical change and errors excepted

