

Product information

97 33 01

KNIPEX MultiCrimp®

Lever Action Crimping Pliers with changer magazine


- Just one tool for the most common crimping applications
- Crimping dies changed quickly and easily without any additional tool
- Sorted and protected storage of the interchangeable dies in a round magazine
- Comfortable, powerful crimping pliers in professional quality
- Same reliable crimping results as with fixed crimping dies
- Consistently high crimping quality thanks to precision dies and forced locking mechanism (unlockable)
- Chrome vanadium electric steel in special quality, oil-hardened
- Round magazine: plastic, fibreglass-reinforced




General

Article No.	97 33 01
EAN	4003773066927
Pliers	burnished
Handles	with multi-component grips
Weight	770 g
Dimensions	250 x 75 x 28 mm
Reach	yes
RohS	no


Technical details



Applications	non-insulated open plug type connectors (plug width 4.8 + 6.3 mm)
Capacity in square millimetres	0.5 — 6.0 mm ²
Number of crimping positions	3
AWG	20 — 10



Applications	insulated terminals, plug connectors + butt connectors
Capacity in square millimetres	0.5 — 6.0 mm ²
Number of crimping positions	3
AWG	20 — 10



Applications	Wire ferrules
Capacity in square millimetres	0.25 — 6.0 mm ²
Number of crimping positions	5
AWG	24 — 10

Classification	
eCl@ss 5.1.4	21040301
ETIM 5.0	EC000168
ETIM 6.0	EC000168
proficl@ss 6.0	AAA946c003
UNSPSC 13.1	27112147
Accessories	
97 39 05	Crimping die for non-insulated open plug type connectors (plug width 4.8 + 6.3 mm),
97 39 09	Crimping die for insulated and non-insulated wire ferrules,
97 39 13 A	Crimping die for non-insulated crimp terminals, tube and compression cable lugs in accordance with DIN 46234 and DIN 46235 and non-insulated crimp, butt and press connectors in accordance with DIN 46341 and DIN 46267,
97 39 06	Crimping die for insulated terminals, plug connectors and butt connectors,
97 39 08	Crimping die for insulated and non-insulated wire ferrules,
97 39 13	Crimping die for non-insulated crimp terminals, tube and compression cable lugs in accordance with DIN 46234 and DIN 46235 and non-insulated crimp, butt and press connectors in accordance with DIN 46341 and DIN 46267,
97 39 90	Changer magazine empty,

technical change and errors excepted



Changing the crimping dies: unlock the magazine position, take out the set of dies which the pliers have been pushed on



Changing position: service lever opens out for parallel jaw positioning



Fold in the service lever and press the pliers – ready for use again



