

Product information

98 25 02 SLS

(Slim) PlusMinus screwdriver

Pozidriv®

IEC 60900 DIN EN 60900

- Driving tips for PlusMinus profile screws
- Use with electronics installation components, e.g. automatic circuit breakers
- Reduced blade isolation diameter for recessed spring and screw elements
- Ergonomically optimised dual component handle for fatigue reduced work and optimum transmission of force
- Handle design prevents rolling
- Chrome vanadium molybdenum steel



⚡ 1000 V ⚡

General

| | |
|-------------|---|
| Article No. | 98 25 02 SLS |
| EAN | 4003773081067 |
| point | burnished |
| Handles | insulating multi-component handle, VDE-tested |
| Weight | 89 g |
| Dimensions | 212 x 33 x 35 mm |
| Standard | DIN EN 60900 IEC 60900 |
| Reach | no |
| RohS | no |

Technical details

| | |
|-------------------------------|--------|
| Size | PZ/S 2 |
| Blade length | 100 mm |
| Handle length | 118 mm |
| Length of non-insulated blade | 18 mm |
| VDE tested | yes |

Classification

| | |
|----------------|------------|
| eCl@ss 5.1.4 | 21040401 |
| ETIM 5.0 | EC000144 |
| ETIM 6.0 | EC000144 |
| proficl@ss 6.0 | AAA818c006 |
| UNSPSC 13.1 | 27111701 |

technical change and errors excepted

Pozidriv® is a registered trademark of European Ind. Serv. Ltd.

