Series 7400 Kraftform pistol handle, pre-set adjustable torque screwdrivers (3.0-8.8 Nm) with Rapidaptor quick-release chuck, 7462 x 3.0 Nm x 3.0-6.0 Nm Series 7400 Kraftform Torque Screwdrivers, with a factory pre-set measurement value













	Factory	pro oct torque	aarouudriuar	with	nistal bandla
•	Iduluiy	pre-set torque	SCIEWUIIVEI	VVILII	pisioi nanule

- Rapidaptor quick-release chuck
- Rapidaptor technology for rapid bit change
- Suitable for bits with 1/4" hex head drive
- Distinct signal when pre-set value is reached

Wera torque screwdriver. Kraftform pistol handle for particularly high torque transmission, multi-component for high working speeds and particularly ergonomic screwdriving. With a factory pre-set torque value set to the smallest scale value. For all applications, where the same constant torque and repeat accuracy are required. The torque can be changed with an extra tool within the measuring range (re-calibration kit can be ordered with the code number 05137002001). Afterwards you can check the set value using an off-the-shelf torque tester. Unlimited loosening torque for slackening stuck screws. Rapidaptor quick-release technology for rapid bit changes. Suitable for bits with a 1/4" external hexagon drive as per DIN ISO 1173-C 6.3 and E 6.3 (ISO 1173). Multi-component Kraftform handle with hard and soft zones for high working speeds, whilst being easy on the hand. Please note: 1 Ncm = 0.01 Nm.

Web link

https://products.wera.de/en/torque\_tools\_series\_7400\_kraftform\_torque\_screwdrivers\_with\_a\_factory\_pre-set\_measurement\_value\_7400\_pre-set\_pistol\_handle.html

Series 7400 Kraftform pistol handle, pre-set adjustable torque screwdrivers (3.0-8.8 Nm) with Rapidaptor quick-release chuck, 7462 x 3.0 Nm x 3.0-6.0 Nm Series 7400 Kraftform Torque Screwdrivers, with a factory pre-set measurement value





Pre-set, adjustable torque screwdrivers

Pre-set, adjustable torque screwdrivers

Wera torque screwdrivers. With a

factory pre-set torque value set to

the smallest scale value. For all

applications, where the same


accuracy are required. The torque can be changed with an extra tool within the measuring range (recalibration kit can be ordered with the code number 05137002001). Afterwards you can check the set value using an off-the-shelf torque

torque and repeat

constant

tester.

Unlimited torque



Unlimited torque for loosening seized screws.

## Versatile



Rapidaptor technology makes the tool adaptable since bits and sockets can be exchanged rapidly.

## Chuck-all



The Rapidaptor quick-release chucks hold 1/4" DIN ISO 1173-C 6,3 and E 6,3 as well as Wera series 1 and 4 bits.

## Rapid-in and self-lock



The bit can be pushed into the adaptor without moving the sleeve. The lock is activated automatically as soon as the bit is applied to the screw. Bits are held securely and wobble-free.

Rapid-out



Simply push the sleeve forward to change the bit. The spring mechanism lifts the bit off the magnet and unlocks the tool. The bit can be easily removed. The rapid-out function makes it easy to remove even the smallest bits without extra tools. Single-hand function



Every function of the Rapidator quick-release chuck, such as inserting or releasing bits, can be carried out with one hand. This is faster, more economical and more ergonomic. There are no unnecessary manoeuvres.

Web link

https://products.wera.de/en/torque\_tools\_series\_7400\_kraftform\_torque\_screwdrivers\_with\_a\_factory\_pre-set\_measurement\_value\_7400\_pre-set\_pistol\_handle.html

Wera - 7400 pre-set, pistol handle 05074717001 - 4013288102935 Wera Werkzeuge GmbH Korzerter Straße 21-25 D-42349 Wuppertal Tel: +49 (0)2 02 / 40 45-0 E-Mail: info@wera.de Series 7400 Kraftform pistol handle, pre-set adjustable torque screwdrivers (3.0-8.8 Nm) with Rapidaptor quick-release chuck, 7462 x 3.0 Nm x 3.0-6.0 Nm Series 7400 Kraftform Torque Screwdrivers, with a factory pre-set measurement value



Further versions in this product family:

			╟┅╫╷┅╢	<b> +++</b> + <b>1</b> ++++				
	art. no.	inch	Nm	Nm	mm	mm	inch	inch
05074717001	7462	1/4	3.0	3.0-6.0	150	100	6	4
05074728001	7463	1/4	4.0	4.0-8.8	150	100	6	4